

K19 - Series Scrubbers



Tank Material:	Poly 5/16" (7.9mm)				
Chassis Construction:	3/16" Steel (4.8mm) Powder Coated Steel				
Front Wheels (Diameter x Width):	(2x) 10" x 2.5" (25.4 x 6.4cm) - Black				
Rear Casters (Diameter x Width):	(2x) 2.5" x 1.38" (6.4 x 3.5cm) - Black				
Length x Width x Height	53 x 29 x 38.5 in *				
<small>*Dimensions listed are for the largest width deck configuration and squareness removed from the machine.</small>	135 x 74 x 98 cm *				
Scrub Motor(s):	0.75 hp / 559 watts		1.5 hp / 1,100 watts	0.75 hp / 559 watts	
Brush RPM:	270 rpm		2,500 rpm	270 rpm	
System Voltage:	24 VDC				
Standard Battery:	175 ah WET				
Battery Run Time:**	Up to 3.5 Hours				
Charger:	120VAC / 60 Hz Input - 24VDC / 12 amp Output				
Traction Drive System:	0.5hp - All Gear / Sealed (373 watts)				
Solution Tank Capacity:	19 gal / 72 L				
Solution Flow / Filter:	0 - 0.6 GPM / Stainless Inline (0 - 2.3 LPM)				
Recovery Tank Capacity:	19 gal / 72 L				
Vacuum Motor:	0.8 hp / 36V / 3 Stage / 640 watts				
Vacuum Water Lift:	70" / 178 cm / 70 cfm				
Squeegee:	37 in (94 cm)	41 in (104 cm)	37 in (94 cm)		
Sound Levels:**	66 dBA**				
Productivity - Theoretical:***	25,979 ft2/hr 2,414 m2/hr	28,000 ft2/hr 2,601 m2/hr	24,000 ft2/hr 2,229 m2/hr	28,000 ft2/hr 2,601 m2/hr	25,979 ft2/hr 2,414 m2/hr
Productivity - Practical:***	12,061 ft2/hr 1,121 m2/hr	13,000 ft2/hr 1,208 m2/hr	11,132 ft2/hr 1,034 m2/hr	13,000 ft2/hr 1,208 m2/hr	12,061 ft2/hr 1,121 m2/hr



Location:
Kodiak Cleaning Equipment
1711 South Street
Racine, WI
53404

Phone:
262-833-4025

Email:
customerservice@kodiakequip.com
Website:
www.kodiakequip.com

Specifications subject to change without notice.
*Battery Run Times are based on continuous scrubbing run times, standard batteries, low down pressure and all options off.
**Decibel levels for Disk per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

***Productivity is based off of ISSA 2010 Cleaning Times