

## K25 - Series Scrubbers



Tank Material:	Poly 5/16" (7.9mm)					
Chassis Construction:	3/16" Steel (4.8mm) Powder Coated Steel					
Front Wheels (Diameter x Width):	(2x) 10" x 2.5" (25.4 x 6.4cm) - Black					
Rear Casters (Diameter x Width):	(2x) 2.5" x 1.38" (6.4 x 3.5cm) - Black					
Length x Width x Height	62 x 33 x 39.5 in *					
<small>*Dimensions listed are for the largest width deck configuration and squeegees removed from the machine</small>	157 x 84 x 100 cm*					
Scrub Motor(s):	0.75 hp / 559 watts	1.5 hp / 1,100 watts		0.75 hp / 559 watts		
Brush RPM:	270 rpm	2,500 rpm		270 rpm		
System Voltage:	36 VDC					
Standard Battery:	150 ah WET					
Battery Run Time:**	Up to 4 Hours					
Charger:	120VAC / 60 Hz Input - 36VDC / 25 amp Output					
Traction Drive System:	0.75hp - All Gear / Sealed (559 watts)					
Solution Tank Capacity:	25 gal / 95 L					
Solution Flow / Filter:	0 - 0.75 GPM / Stainless Inline (0 - 2.8 LPM)					
Recovery Tank Capacity:	26 gal / 98 L					
Vacuum Motor:	0.8 hp / 36V / 3 Stage / 640 watts					
Vacuum Water Lift:	70" / 178 cm / 70 cfm					
Squeegee:	41 in (104 cm)					
Sound Levels:**	66 dBA**					
Productivity - Theoretical***	28,000 ft <sup>2</sup> /hr 2,601 m <sup>2</sup> /hr	31,915 ft <sup>2</sup> /hr 2,965 m <sup>2</sup> /hr	24,000 ft <sup>2</sup> /hr 2,230 m <sup>2</sup> /hr	28,000 ft <sup>2</sup> /hr 2,601 m <sup>2</sup> /hr	27,027 ft <sup>2</sup> /hr 2,510 m <sup>2</sup> /hr	30,000 ft <sup>2</sup> /hr 2,787 m <sup>2</sup> /hr
Productivity - Practical***	13,000 ft <sup>2</sup> /hr 1,208 m <sup>2</sup> /hr	14,851 ft <sup>2</sup> /hr 1,380 m <sup>2</sup> /hr	11,143 ft <sup>2</sup> /hr 1,035 m <sup>2</sup> /hr	13,000 ft <sup>2</sup> /hr 1,208 m <sup>2</sup> /hr	12,526 ft <sup>2</sup> /hr 1,163 m <sup>2</sup> /hr	14,000 ft <sup>2</sup> /hr 1,300 m <sup>2</sup> /hr



**Location:**  
Kodiak Cleaning Equipment  
1711 South Street  
Racine, WI  
53404

**Phone:**  
262-833-4025

**Email:**  
[customerservice@kodiakequip.com](mailto:customerservice@kodiakequip.com)  
**Website:**  
[www.kodiakequip.com](http://www.kodiakequip.com)

\*Battery Run Times are based on continuous scrubbing run times, standard batteries, low foam pressure and all options off.  
\*\*Decibel levels for Disk per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OEMA  
\*\*\*Productivity is based off of OSHA 2010 Cleaning Times  
Specifications subject to change without notice.